



HEAVY DUTY DEGREASING POWDER – TECHNICAL DATA SHEET

Description

An alkaline detergent powder, coloured yellow, designed for cleaning in areas where high degree of oil and grease are encountered, such as catering, engineering and food processing. This product contains surfactants considered by our suppliers to be >80% biodegradable when tested by the OECD screening test which satisfies EEC directives 82/242 and 82/243.

Product Code HDY

The Control of Substances Hazardous to Health Regulations 2002 (COSHH)

For a Safety Data Sheet on this product please contact Confederate Chemicals by telephone, or by e-mail at lab@confederatechemicals.co.uk

Instructions for use

FRYERS Turn off heaters and allow the oil temperature to drop until only warm. Drain the oil into a clean dry receptacle. Partly fill the fryer with water. Add HEAVY DUTY DEGREASING POWDER at the rate of 50gm/litre. Bring the solution to the boil and simmer for half an hour. Simultaneously immerse all the frying baskets to clean. Turn off heaters and allow to cool to around 40°C. Use a stiff brush to clean all surfaces including the surround. Drain the fryer and rinse thoroughly with water. Dry with disposable paper. Refill with oil and return fryer to use.

BRATT PANS Turn off heat supply. Empty pan of all contents. Part fill the pan with a 50gm/litre solution of HEAVY DUTY DEGREASING POWDER made up with hot water. Clean the internal surfaces thoroughly. Drain the solution, rinse thoroughly and dry.

EXTRACTOR FILTERS Remove the filters and soak overnight in a 100gm/litre solution of HEAVY DUTY DEGREASING POWDER made up with hot water. Rinse thoroughly with hot water and allow to dry.

GENERAL WASHING Use at the rate of 3 to 12gm/litre of hot water, depending upon soiling.

DEGREASING MACHINERY AND CATERING EQUIPMENT Using at 12 to 25gm/litre of hot water.

Equipment

Avoid prolonged contact with aluminium at high solution strengths.