



SAFETY DATA SHEET

SMOKE CLOAK

Page: 1

Compilation date: 31/05/2006

Revision date: 15/03/17

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: SMOKE CLOAK

Product code: A975

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Liquid alkaline solution.

1.3. Details of the supplier of the safety data sheet

Company name: Confederate Chemicals Ltd

Mochdre Industrial Estate

Newtown

Powys

SY16 4LE

Tel: 01686 627158

Email: lab@confederatechemicals.co.uk

1.4. Emergency telephone number

Emergency tel: 01686 627158

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Carc. 2: H351; Skin Corr. 1A: H314

Most important adverse effects: Causes severe skin burns and eye damage. Suspected of causing cancer.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

H351: Suspected of causing cancer.

Hazard pictograms: GHS05: Corrosion

GHS08: Health hazard



Signal words: Danger

Precautionary statements: P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

[cont...]

SAFETY DATA SHEET

SMOKE CLOAK

Page: 2

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SODIUM HYDROXIDE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-185-5	1310-73-2	-	Skin Corr. 1A: H314	10-30%

LAKELAND AMA

290-476-8	90170-43-7	-	-	1-10%
-----------	------------	---	---	-------

TRISODIUM NTA POWDER

-	-	-	Acute Tox. 4: H302; Eye Irrit. 2: H319; Carc. 2: H351	1-10%
---	---	---	--	-------

Contains: and
Amphoteric surfactant.

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

[cont...]

SAFETY DATA SHEET

SMOKE CLOAK

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Irritation or pain may occur at the site of contact. Blistering may occur. Severe burns may occur.

Eye contact: There may be irritation and redness. The eyes may water profusely. Corneal burns may occur.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Corrosive burns may appear around the lips. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be a feeling of tightness in the chest with shortness of breath. Exposure may cause coughing or wheezing. There may be congestion of the lungs causing severe shortness of breath. There may be loss of consciousness.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Alcohol or polymer foam. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a suitable container. Wash down the drain with large amounts of water.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

[cont...]

SAFETY DATA SHEET

SMOKE CLOAK

Page: 4

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

SODIUM HYDROXIDE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	-	-	FED

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Suitable respiratory protection must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety goggles. Face-shield. Ensure eye bath is to hand.

Skin protection: Protective clothing with elasticated cuffs and closed neck. Boots made of PVC. Ensure safety shower is to hand.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Miscible in all proportions

Flash point°C: None

Relative density: 1.28 - 1.30

pH: 12.5 - 14 (1% sol.)

9.2. Other information

Other information: No data available.

[cont...]

SAFETY DATA SHEET

SMOKE CLOAK

Page: 5

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

10.5. Incompatible materials

Materials to avoid: Aluminium. Magnesium.

10.6. Hazardous decomposition products

Haz. decomp. products: Potassium Hydroxide reacts with Aluminium and Magnesium with the evolution of Hydrogen, especially in the presence of water. Hydrogen can form explosive mixtures in air.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

SODIUM HYDROXIDE

IPR	MUS	LD50	40	mg/kg
ORL	RBT	LDLO	500	mg/kg

TRISODIUM NTA POWDER

ORL	RAT	LD50	1450	mg/kg
-----	-----	------	------	-------

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Carcinogenicity	--	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Irritation or pain may occur at the site of contact. Blistering may occur. Severe burns may occur.

Eye contact: There may be irritation and redness. The eyes may water profusely. Corneal burns may occur.

[cont...]

SAFETY DATA SHEET

SMOKE CLOAK

Page: 6

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Corrosive burns may appear around the lips. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be a feeling of tightness in the chest with shortness of breath. Exposure may cause coughing or wheezing. There may be congestion of the lungs causing severe shortness of breath. There may be loss of consciousness.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

TRISODIUM NTA POWDER

DAPHNIA	48H EC50	780	mg/l
FISH	96H LC50	98	mg/l

12.2. Persistence and degradability

Persistence and degradability: Material contains chelating agents considered biodegradable by our suppliers.

12.3. Bioaccumulative potential

12.4. Mobility in soil

Mobility: Soluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Contains no substance classified as Dangerous for the Environment in the Chemicals (Hazard Information and Packaging) Regulations 2002, or subsequent amendments.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Normal use, weak, neutral solutions may be discharged to the sewer. Ensure discharges are within Water Authority consent limit. Flush down drain with plenty of water.

Recovery operations: Dispose of in accordance with local and national regulations.

Disposal of packaging: All residues must be removed from packaging prior to disposal as controlled waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

[cont...]

SAFETY DATA SHEET

SMOKE CLOAK

Page: 7

14.1. UN number

UN number: UN1719

14.2. UN proper shipping name

Shipping name: CAUSTIC ALKALI LIQUID, N.O.S. (Sodium Hydroxide, Trisodium Nitrilotriacetate)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: Refer to the Manual Handling Operations Regulations 1992.

Store in accordance with HSE Guidance Note CS17.

Classed as special waste by the Hazardous Waste Regulations 2005.

Read in conjunction with the Technical Data sheet concerning use of the product.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H319: Causes serious eye irritation.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. This Safety Data Sheet and the formulation behind it are the property of Confederate Chemicals GRP Ltd and are used under licence by Confederate Chemicals Ltd.